

SDS6015HP SERIES

Low Profile Shielded Power Inductors




RoHS Compliant

PART NUMBERING SYSTEM

SDS	6015HP	—	3R3N	—	LF
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

SHAPES AND DIMENSIONS


UNIT : mm



A=6.3 Max. B=6.3 Max. C=4.8 D=1.65 Max. E=2.0 F=0.6

RECOMMENDED PATTERNS

UNIT : mm



G= 4.60 H= 2.60 I = 1.00

FEATURES

- Low profile (6.2x6.3 max. square. 1.65mm max. height).
- Magnetically shielded construction and low DC resistance.
- Suitable for large current.
- Ideal for a variety of DC-DC converter inductor application.
- Lead Free and RoHS Compliant.

SDS6015HP SERIES

Low Profile Shielded Power Inductors




RoHS Compliant

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	DCR (m Ω) (Max.)	Isat (A) (Max.)	Irms (A) (Max.)	TEST FREQ. (f)
SDS6015HP-R60N-LF	0.6 $\pm$ 30%	22	6.00	3.90	100KHz
SDS6015HP-R90N-LF	0.9 $\pm$ 30%	27	5.00	3.50	100KHz
SDS6015HP-1R4N-LF	1.4 $\pm$ 30%	40	3.90	2.80	100KHz
SDS6015HP-2R0N-LF	2.0 $\pm$ 30%	57	3.20	2.30	100KHz
SDS6015HP-3R3N-LF	3.3 $\pm$ 30%	96	2.60	1.70	100KHz

- Isat : DC current at which the inductance drops 35%(typ) from its value without current.
- I rms : : Average current for 40°C temperature rise from 20°C ambient.
- Operating temperature range -40°C to +125°C , Electrical specifications at 25°C .
- PLATING / SOLDER : TIN-SILVER-COPPER (95.5%/4.0%/0.5%)

PACKAGING SPECIFICATION



STAYLE	Q' TY (PCS)	DIMENSIONS (m/m)					
		Ao	Bo	Ko	P	Po	D $\pm$ 0.3
13"	2,000	5.72	5.72	1.85	8.00	4.00	12.0